

IN THE SPECIFICATION

Referring to the Substitute Specification, please replace paragraph [0013] of the Substitute Specification, with the following new paragraph [0013]:

[0013] a plurality of side walls depending from at least half of the edges of said main panel, said edges having sidewalls hereinafter referred to as remaining edges, ~~said side walls enclosing a space;~~

Referring to the Substitute Specification, please replace paragraph [0014] of the Substitute Specification, with the following new paragraph [0014]:

[0014] wherein one or more of said side walls includes an outer wall panel and an inner wall panel, said outer wall panel extending from a proximal fold or score line along a remaining edge and said inner wall panel extending from a distal fold or score line remote from the proximal fold or score line and along an opposed edge of said outer wall panel, the combination of panels [[to]] forming a roll-over wall; and

Referring to the Substitute Specification, please replace paragraph [0015] of the Substitute Specification, with the following new paragraph [0015]:

[0015] wherein one or more of said roll-over walls further include one or more removable portions operatively removable ~~from~~ to leave a remaining wall portion such that the enclosing and/or strength properties of the container remain substantially unaffected upon removal of any one or more of said removable portions.

Referring to the Substitute Specification, please replace paragraph [0018] of the Substitute Specification, with the following new paragraph [0018]:

[0018] a plurality of side walls depending from at least half of the edges of said main panels other than those in common with the hinge line, said edges having sidewalls hereinafter referred to as remaining edges, said side walls and said joining panel enclosing a space between said main panels when said main panels are pivoted towards one another to define the enclosed space;

Referring to the Substitute Specification, please replace paragraph [0019] of the Substitute Specification, with the following new paragraph [0019]:

[0019] wherein one or more of said side walls includes an outer wall panel and an inner wall panel, said outer wall panel extending from a proximal fold or score line along a remaining edge and said inner wall panel extending from a distal fold or score line remote from the proximal fold or score line and along an opposed edge of said outer wall panel, the combination of panels ~~[[to]]~~ forming a roll-over wall; and

Referring to the Substitute Specification, please replace paragraph [0020] of the Substitute Specification, with the following new paragraph [0020]:

[0020] wherein one or more of said roll-over walls further include one or more removable portions operatively removable ~~from~~ to leave a remaining wall portion such that the enclosing and/or strength properties of the container remain substantially unaffected upon removal of any one or more of said removable portions.